

## WEST SYSTEM

### West System Epoxy Products 105 Epoxy Resin

105 Resin is the base material of the West System family of products, on which all of the compounds are built. The resin is a clear, pale amber, low-viscosity liquid epoxy resin. Formulated for use with West System hardeners, it can be cured in a wide temperature range to form a high-strength solid with excellent moisture resistance. It is designed specifically to wet out and bond with wood fiber, fiberglass, reinforcing fabrics and a variety of metals. An excellent adhesive, 105 will fill gaps and bridge voids when modified with West System filler and can be sanded and shaped when cured. With roller applications, it possesses excellent thin-film characteristics to flow out and self-level without "fish-eyeing". The resin cures clear so that you can achieve a natural finish when coating with varnish. It has a relatively high flash point and no strong solvent odor, making it safer to work with than polyesters.

Order No	Mfg No	Size	List
108180	105-A	Quart	\$44.22
108181	105-B	.98 Gallon	\$99.73



## WEST SYSTEM

### 205 Epoxy Hardener

A medium-viscosity epoxy curing agent. It is used in a majority of situations, at lower temperatures and to produce a rapid cure that develops its physical properties quickly at room temperature. When mixed with the 105 Resin in a five-part resin to one-part hardener ratio, the cured resin/hardener mixture yields a rigid, high-strength, moisture-resistant solid with excellent bonding and coating properties. Mixing ratio is 5:1. Potlife at 72° F: 9 to 12 minutes  
Cure to a solid state: 6 to 8 hours  
Cure to maximum strength: 1 to 4 days.  
Minimum recommended temperature: 40°F

Order No	Mfg No	Size	List
108184	205-A	7 oz.	\$26.29
108185	205-B	27.5 oz.	\$48.89



## WEST SYSTEM

### 206 Slow Epoxy Hardener

For use when extended working and cure time is needed or to provide adequate working time at higher temperatures. Not recommended for clear coating. Mixing ratio is 5:1. Potlife at 72° F: 20 to 25 minutes  
Cure to a solid state: 9 to 12 hours  
Cure to maximum strength: 1 to 4 days.  
Minimum recommended temperature: 60°F

Order No	Mfg No	Size	List
108182	206-A	7 oz.	\$26.29
108183	206-B	27.5 oz.	\$48.89



## WEST SYSTEM

### 209 Tropical Epoxy Hardener

A general purpose hardener used in extremely warm and humid conditions. Mixing ratio is 3:1. Potlife at 95° F: 15 to 20 minutes; at 72° F: 40 to 50 minutes.  
Cure to a solid state at 95° F: 6 to 8 hours.  
Cure to maximum strength: 1 to 4 days.  
Minimum recommended temperature: 70°F

Order No	Mfg No	Size	List
333510	209-SA-X	.66 Pt.	\$38.49
333527	209-SB	.33 Gal.	\$84.59



# Maintenance

## WEST SYSTEM EPOXY PRODUCTS

## WEST SYSTEM

### 207 Special Clear Hardener

Developed for coating and fiberglass cloth application where an exceptionally clear, moisture-resistant, natural wood finish is desired. 207 Hardener will not blush or turn cloudy in humid conditions. Thin film applications roll out and tip off smoothly, requiring less sanding in preparation for finish coatings. Three coats or more can be applied in one day without additional surface preparation. Fewer coats are required to fill fiberglass weave and in most cases the final coating can be sanded the following day.

105/207 has strong physical properties, so it can be used as a structural adhesive for gluing and laminating. It has excellent compatibility with paints and varnishes. An ultraviolet inhibitor in 207 helps provide a beautiful, long lasting finish when used with quality UV filtering varnish. 105/207 cures clear and colorless.

Order No	Mfg No	Size	List
333659	207-SA	.66 Pt.	\$44.29
333661	207-SB	.33 Gal.	\$92.69



## WEST SYSTEM

### Mini Pump System Set

For dispensing of West System brand 105 resin and 205, 206, 207 and 209 hardeners. Mounts directly on the resin and hardener containers and eliminates the mess involved with measuring by weight or volume. Calibrated to deliver the proper working ratio of 5 parts resin to 1 part hardener with one full pump stroke of resin for each one full pump stroke of hardener or 3 parts of resin to 1 part hardener with one full pump stroke. Made of polypropylene. May be left mounted in resin and hardener cans. Pumps from sizes A, B and C West System Resins and Hardeners.

Order No	Mfg No	List
333572	300	\$19.59



## WEST SYSTEM

### 403 Microfibers Gap Filler

A fine fiber blend used as a thickening additive with resin/hardener to create a multi-purpose adhesive, especially for bonding wood. Epoxy thickened with microfibers provides good gap-filling qualities while retaining excellent wetting/penetrating capabilities. Color: off-white. 6 oz. can.

Order No	Mfg No	List
108191	403-9	\$12.89



## WEST SYSTEM

### 404 High Density Filler

Creates a thickened adhesive with excellent compressive strength. For hardware bonding and other applications requiring a strong interface between different materials. 15.2 oz. canister.

Order No	Mfg No	List
333447	404-15	\$16.99



## WEST SYSTEM

### 405 Filling Blend Filler

This strong, wood-toned filler is good for use in glue joints and fillets on naturally finished wood. It mixes easily with epoxy and lets you create fillets that are smooth and require little sanding. Its color is a consistent brown, so 405 can be used to modify the shade of other West System fillers. 8 oz. can.

Order No	Mfg No	List
333672	405	\$18.79



## WEST SYSTEM

### 406 Colloidal Silica Filler

Thickening additive used to control the viscosity of the epoxy and prevent epoxy runoff in vertical and overhead joints. 406 is a very strong filler that creates a smooth mixture, ideal for general bonding and filleting. It is also the most versatile filler in the West System. Often used in combination with other fillers, it can be used to improve strength, abrasion resistance, and consistency of fairing compounds, resulting in a tougher, smoother surface. Color: off-white.

Order No	Mfg No.	Size	List
333683	406-2	1.7 oz.	\$12.99
333694	406-7	5.5 oz.	\$30.59



## WEST SYSTEM

### 407 Low Density Filler

Creates an easily sanded fairing and surfacing compound. Cures to a rigid, lightweight material with good load-bearing strength for its weight. 4 oz. canister.

Order No	Mfg No	List
333458	407-5	\$19.79



## WEST SYSTEM

### 410 Microlight Ultra-Light Fairing Compound

The ideal low-density filler for creating a light, easily-worked fairing compound especially suited for fairing large areas. Microlight™ mixes easily and is easier to sand than microballs. Feathers to a fine edge and is also more economical for large fairing jobs. Not recommended under dark paint or other surfaces subject to high temperatures. Cures to a tan color.

Order No	Mfg No	Size	List
108189	410-2	2 oz.	\$18.79
108190	410-7	5 oz.	\$37.92



## WEST SYSTEM

### West System Six10 Thickened Epoxy Adhesive

A two-part thickened epoxy adhesive in a convenient, self-metering cartridge. For permanent, waterproof, structural gap-filling and gluing. Bonds to wood, fiberglass, metals and masonry. With the included 600 Static Mixer attached you can dispense fully mixed adhesive right where you need it using a standard caulking gun. Working time is 42 minutes at 72°F, cures to a solid in 5-6 hours and takes high loads in 24 hours. Contains 190 ml of resin and hardener.

Order No	Mfg No	List
333604	610	\$26.29



### Extra Static Mixing Wand (2 Pack)

Order No	Mfg No	List
333615	600-2	\$6.69

# Maintenance

WEST SYSTEM EPOXY PRODUCTS • EVERCOAT FINISH RESIN • TABLE TOP RESIN • EPOXY PASTE



### 650-8 G/flex Epoxy

A toughened, versatile, liquid epoxy for permanent waterproof bonding of fiberglass, ceramics, metals, plastics, damp and difficult-to-bond woods. With a modulus of elasticity of 150,000 PSI, it is a bit more flexible than standard epoxies and polyester, but much stiffer than adhesive sealants. This gives G/flex the ability to make structural bonds that can absorb the stress of expansion, contraction, shock and vibration. It is ideal for bonding dissimilar materials. It can be modified with West System fillers and additives, and used to wet-out fiberglass tapes and fabrics. Mixed at a 1:1 ratio, G/flex gives you 45 minutes of working time at room temperature. It reaches an initial cure in 7 to 10 hrs and full cure in 24 hrs. 8 oz. kit (2 4 oz. bottles).

Order No	Mfg No	List
333626	650-8	\$28.09



### G/5 Five-Minute Adhesive

An easy to use, 2-part resin/hardener system for quick repairs, tooling and general bonding. May be used in spot applications to hold parts in position while standard epoxy bonds cure. Bonds to wood, fiberglass and metal. Not recommended for long-term bonds subject to high loads or moisture. One-to-one mixture, no pumps are required. Cures in 3-5 minutes.

Order No	Mfg No	Size	List
333593	8654	4 oz. Resin & Hardener	\$26.49



### Plastic Boat Repair Kit

Repair plastic canoes, kayaks and inflatables made from HDPE, LDPE, ABS, PVC or polycarbonate plastic with the contents of this kit. The Plastic Boat Repair Kit features plastic-friendly G/flex 655 epoxy, and is assembled with the do-it-yourselfer in mind. Each Plastic Boat Repair Kit contains 8.4 ounces of pre-thickened G/flex epoxy, protective gloves, mixing pallets and mixing sticks. Illustrated, detailed instructions explain how to repair splits and cracks in plastic boats, attach or repair reinforcement points on inflatable boats and repair pinhole leaks in inflatables. All components are contained in a sturdy, resealable package.

Order No	Mfg No	List
333648	655-K	\$34.99



### Fiberglass Boat Repair Kit

This kit offers the right epoxy, fiberglass and fillers to complete repairs to cracks and holes, gelcoat layers, delaminated cored panels and more. Detailed instructions show users how to make lasting repairs. Each Fiberglass Boat Repair Kit contains eight packets of West System 105 Resin and 205 Hardener, fiberglass fabric, adhesive filler, fairing filler, glue brushes, mixing pots, a mixing stick, an application syringe, three pairs of protective gloves and illustrated instructions for completing a variety of common fiberglass repairs. All components are contained in a sturdy, resealable package that can be easily stowed aboard your boat.

Order No	Mfg No	List
333637	105-K	\$34.99



### G/flex Epoxy Aluminum Boat Repair Kit

Repairs leaky seams and rivets in aluminum boats. This kit contains 4 fl. oz. G/flex 650 resin, 4 fl. oz. G/flex 650 hardener (8 fl. oz. mixed epoxy), 2 reusable mixing stick/applicators, 2 12-cc syringes, 4 grams Adhesive Filler, 4 mixing cups, 1 pr disposable neoprene gloves, 4 alcohol cleaning pans and complete handling and repair instructions.

Order No	Mfg No	List
333585	650-K	\$34.99



### Roller Covers

High-density polyurethane foam roller, ideal for epoxy, paint and varnish application. Can be cut into shorter widths to match the application area and cut into brushes for tipping off fresh coats of epoxy. Covers are 7" wide. 2 per package.

Order No	Mfg No	List
130071	800-2	\$11.39



### Syringe

Reusable syringe that can be loaded with epoxy mixture for injecting into tight spots. Ideal for hardware bonding and plywood repairs. Holds about 1/2 fl. oz. Sold 2 per pack.

Order No	Mfg No	List
107269	807-2	\$7.49



### 804 Reusable Mixing Sticks

A practical mixing, application, filleting, and cleaning tool. Squared, beveled end reaches mixing pot corners for thorough mixing and blending in fillers and for cleaning up excess epoxy. Use rounded end to shape 3/8" radius fillets. Cured epoxy pops off easily, so they can be reused many times. 3/4"-wide x 5-1/2".

Order No	Mfg No.	Per Pack	List
333716	804	8	\$4.79



### 809 Notched Spreader

4" x 4" plastic spreader with 1/8", 3/16" and 1/4" notches on three sides for quickly applying modified epoxy at a constant rate. Useful when laminating large panels.



Order No	Mfg No.	List
333705	809	\$1.59



### Evercoat Marine Finish Resin

The perfect no-run, no-sag polyester resin for marine repairs. An extra-thick, finish coat resin, it cures tack free. May be used on soft woods and fiberglass. Ideal repair for hulls, decks, cabins and tanks. Repairs all boat surfaces, resists impact and protects against moisture. Hardener included.



Order No	Mfg No	Size	List
108008	100554	Pint	\$34.53

### Whitaker Clear Epoxy (Table Top) Resin

Clear epoxy coating for bar tops, tabletops, plaques, etc. Dries to a high gloss finish. Mix ratio: 1 part hardener to 1 part resin.



Order No	Mfg No	Size	List
297364	730010204	Quart Kit	\$49.88



### Evercoat Everflex Epoxy Resin

50/50 mix, all purpose resin for fiberglassing, molding, laminating, repairing or where superior adhesion is required. Used on aluminum, steel, fiberglass, close-grained hardwoods and styrofoam. Packaged in kits of equal portions of resin and hardener.



Order No	Mfg No	Size	List
108032	100643	Quart	\$89.91



### Protective Coating Co. White Epoxy Paste

Heavy duty white epoxy paste can be applied to a dry, wet or underwater surface and will cure to an off white color. Working time of over 1/2 hour. Excellent chemical resistance to mild acids, caustics, detergents, gasoline, fuel oil, salt and fresh water. Will not bond to Teflon, polyethylene and some soft flexible plastics.

Order No	Mfg No	Size	List
333411	08011-5	1/2 lb. can	\$16.99



954-463-4307 • D.S. Hull Company Inc. • www.dshullco.com

# Maintenance

EPOXY SEALER • MARINE TEX • GEL COAT • GLUVIT • POLYESTER GEL PASTE • GEL COAT • COLORING AGENTS



## Starbrite Epoxy Syringe Clear

5 Minute Cure Clear Epoxy  
Convenient self-metering syringe applicator bonds fiberglass, rubber, hard plastic, glass, fabric, ceramic, and metal.  
Fills cracks and holes, mounts components, seals seams.  
Resists most liquids.  
Crystal clear appearance after curing.  
Permanent strength up to 3400 PSI.  
Syringe provides easy even mix of hardener and epoxy for fast application.



Order No	Mfg No	Size	List
231529	93401	1 oz.	\$11.95

## PC Concrete Injectible Repair & Anchoring Epoxy

Two component epoxy gel used for anchoring and concrete repair. Formulated for anchoring threaded rods, bolts, rebar dowels and smooth dowels into concrete, grout filled block and unreinforced masonry. Exceptional strength, maximum field reliability, along with a high heat deflection temperature of 134°. Excellent for filling and repair of cracks in concrete, out performs all caulks and hydraulic cement.



Order No	Mfg No	Size	List
222094	72561	8.6 fl. oz.	\$34.99



## Evercoat Match 'N Patch Gel Coat Repair Kit

Complete set of material for Gel Coat repairs for minor surface damage on boats. Repairs scratches, gouges, cracks, etc. Mixes or matches to any desired color. Kit contains: 1/4 pt. Gel-Paste with hardener, six 1/4 oz. tubes of all primary pigment colors, mixing cup and sticks, cleaning solvent, special release film and instructions.

Order No	Mfg No	List
108034	100668	\$75.97



## Evercoat Scratch Patch

Repair fiberglass boats, bathtubs, shower stalls and hot tubs. Easy permanent repairs on hairline cracks, small scratches and chips in fiberglass. This one part formula does not need a catalyst. Just fill in the crack, let it set and scrape off the excess with the enclosed spreader. It is just that easy. Clear Scratch Patch is ideal for surface scratch repairs of metal flake finish.

Order No	Mfg No	Size	Color	List
108055	105652	.5 oz.	White	\$20.28
108064	105653	.5 oz.	Buff	\$20.28



## Flex Set Epoxy Syringe

Non-sagging, non-shrinking, permanently flexible adhesive.  
Sandable and paintable, FlexSet resists vibration and bending failures by curing to a tough, flexible consistency that creates an air and water tight seal between mating surfaces.

Bonds to PVC, Hypalon®, ceramic, rubber, polyurethane, glass, acrylic, steel, fiberglass, polycarbonate, wood, ABS, aluminum, Lexan® and dissimilar materials.

Apply above or below the waterline, in wet or dry areas. Bonds dissimilar materials like PVC to copper. FlexSet outperforms PVC Cement! Because of the vibration and shock resistance, FlexSet is highly recommended for PVC pipe repairs. As bonded joints shrink and expand, the FlexSet moves with them. Therefore, it won't crack or break from the surface.

Order No	Mfg No	Size	Color	List
202775	RM321C	1 oz.	Sand White	\$28.34



## ITW Philadelphia Resins Marine Tex

High-strength epoxy repair compound designed for filling, bonding and rebuilding wood, fiberglass, ceramic, glass, metal, masonry and many plastics. Easy-to-apply paste makes permanent repairs to hulls, decks, and equipment, including exhaust lines, outdrives, tanks, piping and stringers. Can be used to fill gouges in wood and fiberglass, making repaired area stronger than before. Allows sufficient working time for complex repairs. Bonds dissimilar metals without galvanic corrosion. Can be drilled and tapped. Paintable after cure.

Order No	Mfg No	Size	Color	List
202701	RM305C	2 oz.	White	\$22.12
202703	RM306C	14 oz.	White	\$56.94
202704	RM307C	Quart	White	\$146.64
202702	RM301C	2 oz.	Gray	\$22.12
202705	RM302C	1 lb.	Gray	\$56.94



## Rapid Set Marine Tex

Waterproof epoxy paste is a convenient 1:1 mix for emergency and permanent repairs. Superior bond fills cracks and voids in fiberglass, steel, aluminum, wood, cast iron and many hard plastics. Paintable repair can be drilled, tapped and sanded. Excellent for quick machinery and mechanical repairs to get back underway with minimum downtime. Secures hardware and loose fasteners. Cures in one hour at 72°F.

Order No	Mfg No	Size	List
202728	RM320C	2 oz.	\$16.80



## Gluvit™ Waterproof Epoxy Sealer

Seals and protects hulls and decks. Provides superior protection for fiberglass, wood, aluminum, and steel. Seals leaky seams and rivets in aluminum hulls, and leaks around fiberglass cabins or decks. Hard protective coating flexes with hull movements to bridge and seal hairline cracks.

Order No	Mfg No	Size	List
202711	RM330C	Quart	\$81.20

## Evercoat Polyester Gel Paste

Gel coat quality in a paste. Repair larger areas of gel coat scratches, nicks and gouges. Mix paste with coloring agents to match original color. Neutral paste will make permanent repairs on gel coat and fiberglass panels. Will also adhere to most woods and metal.



Order No	Mfg No	Size	List
109087	100695	Pint	\$43.76



## Whitaker Gelcoat - White - Exterior

With wax. White pigmented polyester gelcoat. Resilient high grade marine gelcoat. Excellent finish coat over all polyester resins, wood, fiberglass, and metals. For repair or fabrication.

Order No	Mfg No	Size	List
297045	601100500	Pint	\$21.25
108080	60110060	Quart	\$26.25
297037	601110800	Gallon	\$90.50



## Evercoat Coloring Agents

Popular coloring agents that blend with polyester resins, gel paste, epoxy resin and other paints and putties.

Order No	Mfg No	Color	Size	List
108010	100503	Red	1 oz.	\$12.71
108012	100505	Yellow	1 oz.	\$12.71
108013	100506	Brown	1 oz.	\$12.71
108014	100507	Admiral Blue	1 oz.	\$12.71
108015	100508	Black	1 oz.	\$12.71
108016	100509	White	1 oz.	\$12.71

Like Us On Facebook

954-463-4307 • D.S. Hull Company, Inc. • www.dshullco.com

# Maintenance

POLYESTER RESIN • FIBERGLASS REPAIR KIT • FIBERGLASS CLOTH - MAT - WOVEN ROVING • MOLD RELEASE WAX



### Polyester Resin

The perfect no-run, no-sag polyester resin for marine, home, and auto repairs. An extra thick finish coat resin, it cures tack free. May be used on soft woods, fiberglass and metal. Ideal repair for hulls, decks, cabins, and tanks. Seals all surfaces, resists impact and protects against dry rot. Hardener included.

Order No	Mfg No	Size	List
108019	600100600	Quart	\$19.75
108020	600100800	Gallon	\$48.75
297023	600100400	5 Gallon	\$223.75



### Premium Polyester Resin

A premium general purpose polyester bonding and laminating resin. For use in boat covering, repair work and laminating. Can be used with pigment and Wax-Sol. Hardener included.

Order No	Mfg No	Size	List
297174	700040601	Quart	\$19.88
297191	700040801	Gallon	\$57.38



### Fiberglass Cloth Tape

Maximum strength tape for small repairs to any surface. Great for use on keels, chines, hull deck corners, etc. Fast wet out formula. Will not rust, rot or unravel along edges.

Order No	Mfg No	Size	List
233241	602000250	2" x 150'	\$0.58
108092	60200450	4" x 150'	\$0.77



### 8 oz. Fiberglass Cloth

The most popular sizes pre-cut in handy sealed plastic packages.

Order No	Mfg No	Size	List
108040	602023801	38" x 1 yd.	\$17.85
108041	602023803	38" x 3 yds.	\$54.60
297331	602023501	50" x 1 yd.	\$24.30
297342	602023503	50" x 3 yd.	\$71.70



### Chopped Fiberglass

1/4" fiberglass chop for a high strength putty. Normally used with Talc or Cab-O-Sil.

Order No	Mfg No	Size	List
297242	605961750	Qt. (Approx.)	\$22.50



### Fiberglass Mat

100% fiberglass in a non-woven state. For bulk build-up when repairing holes and badly damaged areas. Also molds and builds for repair of curved surfaces fiberglass objects (bait and water tanks, etc.)

Order No	Mfg No	Size	Type	List
297308	602034501	50" x 1 yd.	.75 oz.	\$10.35
108043	602033801	38" x 1 yd.	1.5 oz.	\$13.50
108045	602033803	38" x 3 yd.	1.5 oz.	\$29.85
297319	602033501	50" x 1 yd.	1.5 oz.	\$13.50
297320	602033503	50" x 3 yd.	1.5 oz.	\$38.40

### By the Foot; Biaxial Fiberglass Mat (179' roll)

Order No	Mfg No	Width	List
130042	26861	50"	\$4.92



### 24 oz. Woven Roving

Heavyweight fiberglass fabric. Very bulky for stronger repair applications where large buildup is needed. Prepackaged.

Order No	Mfg No	Size	List
108044	602002250	50" x 1 yd.	\$21.75
297353	602002240	38" x 1 yd.	\$17.85



### Wax-Sol

Surfacing agent for polyester resins and gel coats. Makes the surface less tacky for easier sanding. Recommend adding 4 oz. per each gallon of resin.

Order No	Mfg No	Size	List
297253	603100601	4 oz.	\$10.88
297140	603100700	Pint	\$16.88



### Whitaker P.V.A. Mold Release

A one-time parting film. For use in building molds and plugs.

Order No	Mfg No	Size	List
297375	605980600	Quart	\$16.93



### M.E.K.P. (Methyl Ethyl Keytone)

Order No	Mfg No	Size	List
297055	700010903	1/4 oz.	\$4.38
297072	700010901	1 oz.	\$4.88



### Styrene

A general purpose thinner/cleaner. Cleans tools, spray guns and marine hardware. Ideal for thinning epoxies.

Order No	Mfg No	Size	List
108079	160300700	Pint	\$10.50

Like Us On Facebook

954-463-4307 • D.S. Hull Company, Inc. • www.dshullco.com

# Maintenance

FLOTATION FOAM • CABOSIL • SEALANT FOAM • MICROBALOON • MEK SOLVENT • ACETONE

Like Us On Facebook

954-463-4307 • D.S. Hull Company, Inc. • www.dshullco.com

## Cabosil

Thickening agent for polyester resins and gel coats.



Order No	Mfg No	Size	List
297264	604600750	Quart	\$19.50
233243	604700750	Gallon	\$26.70

## Q-Cells

A light weight micro-sphere filler used for soft, easily sanded putties.



Order No	Mfg No	Size	List
297286	604910600	Quart	\$20.40
297123	604910800	Gallon	\$29.85

## Micro-Balloons

Light weight filler for easily sanded putties. Primarily used for fairing compounds.



Order No	Mfg No	Size	List
297275	604610750	Quart	\$24.60



## Whitaker High Load Filler (Talc - Fumed Silica)

Heavy bodied filler used with polyester resins. Makes a moderately strong and hard putty.

Order No	Mfg No	Size	List
297230	605970430	43 oz.	\$23.85



## Plastic Disposable Syringes

Plastic with graduated measuring marks. Comes with plastic protective case. No needle.

Order No	Mfg No	Size	List
265001	SYRDIS20	20 cc	\$1.79
265002	SYRDIS60	60 cc	\$2.99

## EVERCOAT



## Evercoat Sealant Foam

Multiple use foam curing to a semi-rigid, closed cell mass. Can be used on a car, boat or house for caulking, sealing and filling. Will adhere to metal, fiberglass and wood. Waterproof. Cures in 20 minutes. Can be cut, sanded or painted. By the absorption of moisture, expands approximately 50% during cure.

Order No	Mfg No	Size	List
108075	100654	12 oz.	\$29.75



## Dow Great Stuff Gaps & Cracks Foam Sealant

GREAT STUFF™ Gaps & Cracks is a polyurethane-based insulating foam sealant that fills, air-seals and insulates small gaps (up to 1 inch) inside or out.

One 12 oz. can = up to 22 tubes of caulk.



Order No	Mfg No	Size	List
220846	157901	12 oz.	\$7.99



## Floation Foam

Liquid urethane foam. For use in hulls and cavities for floatation or insulation. Not affected by gas or oil. 2.0 lb per cubic foot density.

Order No	Mfg No	Size	List
108084	605622700	2 Quart Kit	\$54.88
108085	605822700	2 Gallon Kit	\$174.88



## Laminating Rollers

Spiral threaded grooves to spread resin and glass better, removes air bubbles and laminates evenly. The angled, tapered, grooved sides give it strength and easy clean-up. Contoured handles for easy holding and easy disassembly for cleaning.

Order No	Mfg No	Size	List
108087	605200900	1/2" x 3"	\$14.88
297089	605300900	3/4" x 3"	\$22.38
297106	605350900	1" x 3"	\$16.88

## Methyl Ethyl Keytone Solvent

An active ketone solvent for cleaning and dissolving epoxy and polyester resins.



Order No	Mfg No	Size	List
108060	580160600	Quart	\$12.00



## Acetone

Polyester cleaner/spray solvent. An excellent cleaner for tools, brushes, and hands.

Order No	Mfg No	Size	List
108061	580010600	Quart	\$8.25
108062	580010800	Gallon	\$25.00



## 3M Acryl-White Putty

Recommended for filling pinholes, scratches and other surface defects on hulls. White color minimizes possibility of color showing through final coat as can happen when using colored putties beneath white paint. Easy to sand, fast drying, spreads easily and has low shrinkage.

Order No	Mfg No	Size	List
202056	05095	14.5 oz.	\$37.63



## Cream Hardener

Precise formula for best cure possible.

Order No	Mfg No	Size	List
369892	27014	4 oz.	\$7.35



## Loctite Tite Foam

New generation of polyurethane-based insulating foam sealant that expands to fill, seal and insulate gaps & cracks inside or out. It is a white polymer foam based on purified & concentrated ingredients that provides 4x more density vs conventional foams for better durability & insulation. It is easy to use and apply with its attached straw applicator and provides a quick durable seal from the elements. Excellent adhesion on most building materials like wood, concrete, stone, metal etc. Product does not contain CFC-propellants.

Order No	Mfg No	Size	List
222681	1988753	12 oz.	\$11.50



# Maintenance

FILLER PUTTY • FIBERGLASS FILLER • AUTO BODY FILLER • JB WELD



### 3m Premium Filler

A vinyl ester filler designed for marine filling and faring applications above and below the waterline. Premium filler resists water absorption into hulls, decks and other fiberglass parts. Easy-to-sand formula with 3M™ Glass Bubbles. Hardener included.

Order No	Mfg No	Size	List
202249	46004	Pint	\$50.41
202256	46005	Quart	\$99.18
202261	46006	Gallon	\$294.89



### Evercoat Skid No More Surface Coating

For steps, porches, walkways, diving boards, docks, boat decks and tools. Skid-No-More is a textured non-skid coating, formulated with acrylic latex and ground rubber. It is non-abrasive, pliable and resilient to the touch. It can be applied to most surfaces with a paintbrush, napped roller or squeegee. Skid-No-More comes in a medium gray color, but can be tinted to a desired color with Evercoat Color Agents.

Order No	Mfg No	Size	List
108035	100854	Quart	\$39.56



### J-B Weld Marine Weld Epoxy

2-part product cures as strong as steel, and is water- and weather-proof.

Can be formed, drilled, ground, tapped, machined, filled, sanded, and painted. It stays pliable for about 30 minutes after mixing, sets in 4-6 hours, and cures fully in 15-24 hours. Before it sets, clean up with soap and water.

Order No.	Mfg. No.	Size	List
277301	8272	2 oz.	\$7.99

Like Us On Facebook

954-463-4307 • D.S. Hull Company, Inc. • www.dsullco.com



### Evercoat Polyester Glazing Putty

Ultra-smooth surfacing putty for finishing off coarse and roughly sanded body filler. Also applies over fiberglass and bare metal. Applies "thin". Won't shrink. Has greater fill capacity. Saves up to 2-1/2 hours over conventional glazing putties. Cures in 20 minutes. Hardener included.

Order No	Mfg No	Size	List
108002	100400	Quart	\$58.85



### Evercoat White Star Filler

The professional's choice conventional autobody filler. Features flexible white plastic formulation with creme hardener. Goes on smoothly, easily and quickly which saves time, trouble and money in all body repairs. Hardener included.

Order No	Mfg No	Size	List
108000	100205	Quart	\$37.00



### J-B Weld Kwik Weld

Not as strong or as heat-resistant as the original J-B WELD. Like metal, it can be formed, drilled, ground, tapped, machined, filled, sanded, and painted. It stays pliable for about 2 minutes after mixing, sets in just 4 minutes, and cures fully in 4 hours. Waterproof and chemical resistant. Before it sets, you can clean up with soap and water.

Order No.	Mfg. No.	Size	List
277325	8276	2 oz.	\$7.99



### 3M Marine High Strength Repair Filler

A unique vinyl ester formulation designed with short strand fiberglass for semi-structural repairs, above and below the waterline.

- Excellent bond strength
- Easy spreading
- Fast curing
- Premixed
- Short strand glass reinforced fibers
- Uses Blue creme hardener.

Order No	Mfg No	Size	List
202283	46012	Pint	\$86.15
202289	46013	Quart	\$131.25



### Evercoat Formula 27 Plastic Filler

Finest quality, extra white plastic filler for filling dents, scrapes, and gouges in wood, metal, fiberglass and concrete. A true "miracle mender" that won't shrink, crack or pop out. A long time favorite of do-it-yourselfers everywhere. Hardener included.

Order No	Mfg No	Size	List
108024	100572	Half Pint	\$21.19
108023	100571	Pint	\$34.45
108022	100570	Quart	\$48.74



### Evercoat Lite Weight Filler

Super light weight auto-body filler that applies without sagging. Lets you file or sand in minutes to seven days later. Requires less sanding to reduce dust and clogging. Feather edges superbly. Cures under humid conditions. Hardener included.

Order No	Mfg No	Size	List
108065	100157	Quart	\$29.72



### USC Duraglas Fiberglass Filler with White Cream Hardener

Repairs fiberglass, metal and wood. Used with fiberglass cloth to cover large holes. Combines resin and chopped fiberglass. Rustproof and waterproof.

Order No	Mfg No	Size	List
369700	24035	Quart	\$38.35
369712	24030	Gallon	\$107.33



### Evercoat America's Cup White Marine Filler

America's Cup White Marine Filler properly applied will quickly and easily repair permanently – breaks, splits, holes, ruptures or other imperfections caused by accidents or normal wear and tear. It can be mixed with universal pigments to match nearly any color. Uses cream hardener (provided) for superior performance.

Order No	Mfg No	Size	List
108053	100574	Gallon	\$112.35



### J-B Weld WaterWeld

Will plug or seal practically anything that leaks. It will patch holes and cracks, and mend almost anything that is broken. It is excellent for rebuilding or fabricating parts, and as an all-purpose adhesive for metals, wood, fiberglass, masonry, ceramics, PVC and ABS. Permanently repair holes, gouges, cuts ... even seals rot in fiberglass and wood. Cures under water. Safe for use on lines carrying potable water.

Can be applied under water; surfaces to be repaired do not need to be clean and dry.

Order No.	Mfg. No.	Size	List
277302	8277	2 oz.	\$8.99

Prices and specifications subject to change without notice.

# Maintenance

ADHESIVE PUTTY • GEL STAIN • J-B WELD EPOXY • SEAL-ALL SEALANT • BLEND STICK

Like Us On Facebook



### J-B Weld ClearWeld Epoxy Syringe

ClearWeld is a quick setting, multipurpose two part epoxy that provides a strong and lasting bond on most surfaces including tile, most plastics, ceramic, glass, wood and metal. ClearWeld is designed to cure with a clear, transparent bond when used at thicknesses of less than 15 mil. ClearWeld has a 1:1 mixing ratio, sets in 5 minutes and will fully cure overnight. With a tensile strength of 3200 PSI, ClearWeld sets to a hard, permanent bond.

Sets in 15 minutes. Cures in 30 minutes. If temperature is below 40°F, then set time is longer.

Order No.	Mfg. No.	Size	List
277336	50112	25 ml	\$7.99

### Seal-All Sealant - Gas and Oil Resistant Sealant

The all-purpose contact adhesive & sealant. In a class of its own, "the repair kit in a tube" is not affected by gasoline, oil, alcohol, water and most solvents, making it ideal for automotive and garage repairs. Seal-All dries fast without sacrificing strength. Dry speed is 2-3 minutes, with a 2-6 hour full cure time, making it perfect for in the garage, around the house or on the go.



Order No	Mfg No	Size	List
333569	380112	2 oz.	\$4.19



### Polyseamseal All Purpose Adhesive Caulk

A premium grade water-based caulk designed to have the strength of an adhesive and the sealing characteristics of a caulk. Loctite Polyseamseal All-Purpose bonds to almost any surface including wood, concrete, metal, ceramic, drywall, plaster and much more. Easy to apply and tool. Environmentally safe, soap and water clean-up. Contains no silicone.

Order No	Mfg No	Size	List
202601	2139006	5.5 oz. Tube	\$4.25
202602	2154751	10 oz. Cartridge	\$6.95



### Starbrite Epoxy Putty Stick

Makes permanent and emergency repairs on fiberglass, wood, metal and plastic. Easy to use; just hand knead until color turns white and apply to damaged area. Product cures under water as well. No boat should be without as this can be the product that saves you from sinking. You never know when a thru hull fitting gets knocked off or a manifold blows, this epoxy stick can save the day and maybe the whole trip.

Order No	Mfg No	Size	List
231586	87104	4 oz.	\$23.78



### DAP® Blend Stick® Value Packs

The fast, easy way to repair nail holes, scratches and other minor blemishes in finished wood surfaces. The four color sticks can be used individually or combined to match any wood tone. Unique teardrop shape makes it easier to use than other blending products. It will not shrink, stain or discolor. For interior use. Each package contains four different color sticks.

Order No	Mfg No	Color	List
200958	04080	Light Woods	\$4.64
200969	04083	Red Woods	\$4.64
200970	04085	Dark Woods	\$4.64



### Starbrite Epoxy Aluminum Stick

Epoxy for emergency and permanent repairs to fuel and water tanks. Makes permanent and emergency repairs on aluminum boats, outdrives, fuel and water tanks and other aluminum parts. Easy to use; just hand knead for 1 minute and apply to damaged area. Product cures under water. Once cured you can drill and tap for screw threads.

Order No	Mfg No	Size	List
231587	87004	4 oz.	\$23.78



### Minwax Gel Stain

A gelled oil-based stain which enhances and beautifies a wide range of surfaces including wood, plywood, veneer, fiberglass, metal and molded fiberboard.

Order No	Mfg No	Color	Size	List
220955	26030	Antique Maple	1/2 Pint	\$9.49
220960	26040	Honey Maple	1/2 Pint	\$9.49
220977	26050	Mahogany	1/2 Pint	\$9.49
220992	26070	Cherry	1/2 Pint	\$9.49



### Famowood Professional Wood Filler

Solvent-based filler which incorporates wood flour enabling it to be sawed, drilled, sanded, planed or nailed just like wood. Virtually no shrinkage, cracking or crumbling. May be used indoors or outdoors.

Order No	Mfg No	Color	Size	List
333534	36141122	Mahogany	1/4 Pint	\$4.99
333556	36141134	Teak/Oak	1/4 Pint	\$4.99



### DAP 100% Silicone Sealant

100% silicone rubber. Won't crack or shrink. Waterproof/weatherproof.

Order No	Mfg No	Color	Size	List
200934	683	White	2.8 oz. Tube	\$8.10
200931	08646	White	9.8 oz. Cartridge	\$6.99
200933	00684	Clear	2.8 oz. Tube	\$8.10
200932	08641	Clear	9.8 oz. Cartridge	\$6.99

### Protective Coating Co. Wood Petrifier Wood Hardener

Single component adhesive, formulated to fully penetrate and revitalize rotted wood. Modern technology has allowed us to develop a water base wood consolidant that is environmentally friendly. Cure for service: overnight. Cure time (max.): 3-7 days.



Order No	Mfg No	Size	List
333435	08444-1	8 oz.	\$8.65
333440	16444-0	16 oz.	\$14.99



### DAP Bluestik Reusable Adhesive Putty

For securing knick-knacks, vases and other decorative items. Net weight 1.0 oz.

Order no.	Mfg. No.	List
120582	01201	\$3.19



### Protective Coating Co. PC-Marine Putty

Hand moldable epoxy putty that is especially designed for emergency repairs where time is of the essence. Work time: 20 min. Cure time: 60 min.

Order No	Mfg No	Size	List
333420	02556-7	2 oz.	\$5.95

954-463-4307 • D.S. Hull Company, Inc. • www.dshullco.com

# Maintenance

5200 MARINE SEALANT • PENETRATING SEALANTS • MARINE SEALANT • SILICONE SEALANT • CAULKS • LEAK SEAL



### Sudbury Elastomeric Penetrating Sealant

Liquid version of Elastomeric Clear Sealant. Low viscosity sealant specially formulated for narrow joints where ordinary sealants cannot reach. Ideal for sealing windshields, portholes, hardware, hatches, vents, and fine deck and cabin seams. Same skinning, curing, adhesive and performance characteristics as Elastomeric Sealant.



Order No	Mfg No	Size	List
280045	350	3 oz.	\$11.25



### Starbrite Silicone Sealant

100% Marine grade silicone, won't turn yellow. Remains flexible from -70° F to +480° F. Bonds to fiberglass, plastic, wood, glass and metal. Unaffected by sunlight, weathering, most chemicals and solvents. Will not shrink or sag. Can be removed easily - excellent for deck hardware.

Order No	Mfg No	Color	Size	List
231551	82101	White	3 oz. Tube	\$13.65
231552	82102	Clear	3 oz. Tube	\$13.65
231553	82103	Black	3 oz. Tube	\$13.65
231554	82121	White	10.3 oz. Cartridge	\$23.78
231555	82122	Clear	10.3 oz. Cartridge	\$23.78
231556	82123	Black	10.3 oz. Cartridge	\$23.78



### 3M Marine 5200 Adhesive/Sealant

This high performance polyurethane adhesive/sealant becomes tack free in 48 hours, cures in 5-7 days with no shrinkage. Remains workable with a trowel or spatula up to four hours after application. Won't sag or flow in vertical or horizontal seams.

Order No	Mfg No	Color	Size	List
201992	05206	White	1 oz. Tube	\$15.05
201818	05203	White	3 oz. Tube	\$24.90
201825	06500	White	10 oz. Cartridge	\$31.75
201993	05205	Black	3 oz. Tube	\$24.90
201859	06504	Black	10 oz. Cartridge	\$41.30
201826	06501	Tan	10 oz. Cartridge	\$24.39
201827	06502	Mahogany	10 oz. Cartridge	\$42.39



### 3M Fast Cure Marine 5200 Adhesive/Sealant

Faster curing version of 5200 Adhesive/Sealant. Becomes tack free in one hour and fully cures in approx. 24 hours. Excellent resistance to weathering, and salt water. Bonds to fiberglass, wood, metal, above and below waterline.

Order No	Mfg No	Color	Size	List
202198	05220	White	3 oz. Tube	\$28.70
202210	06520	White	10 oz. Cartridge	\$47.25



### 3M 4200 Fast Cure Adhesive/Sealant

One-part general all-purpose polyurethane that chemically reacts with moisture to deliver flexible bonds with good adhesion to wood, fiberglass, gelcoat, plastics and metals. Paintable and sandable. Forms watertight weather-resistant seals on joints and boat hardware above or below the waterline.

Order No	Mfg No	Color	Size	List
351094	05260	White	3 oz.	\$24.70
202430	06560	White	10 oz. Cartridge	\$40.95
380438	06564	Black	10 oz. Cartridge	\$40.95



### 3M Fast Cure 4000UV Marine Sealant

One-part sealant that cures to form a firm, rubbery waterproof seal. Its flexibility allows for the dissipation of stress caused by shock, vibration, swelling or shrinking. Designed for marine applications above or below the waterline. Its superior UV resistance properties make this an ideal cosmetic sealant. Color: white. Tack free in 2 hours. Cures in 24 hours.

Order No	Mfg No	Color	Size	List
380405	51135-05280	White	3 oz. Tube	\$23.30
379739	51135-06580	White	10 oz. Cartridge	\$37.90

### Teakdecking Systems

#### SIS 440 Teak Deck Caulking - Black

- The Professional's Choice
- Marine grade
- Adheres permanently
- Remains flexible
- Made in USA
- 10.3 fl. oz. cartridge



Order No	Mfg No	Color	Size	List
121624	SIS440	Black	10.3 fl. oz.	\$27.50



### 3M Marine Silicone Sealant

Remains flexible with excellent resistance to the marine environment. Adheres to bare and painted metal, fiberglass, glass, non-oily woods and many plastics and abraded rubbers. Ideal for head and galley sealing applications. Also excellent gasket adhesive and formed-in-place gasket material.

Order No	Mfg No	Color	Size	List
351068	08017	White	3 oz. Tube	\$19.77
351088	08019	Clear	3 oz. Tube	\$19.77
380416	08027	White	10 oz. Cartridge	\$47.13
380427	08029	Clear	10 oz. Cartridge	\$47.83



### DAP Flexible Clear Sealant

High-performance, elastomeric clear sealant. Excellent adhesion even on damp surfaces. Stays crystal clear and permanently flexible. Excellent UV resistance. Indoor/outdoor use. Cured sealant is mildew resistant. Paintable.

Order No	Mfg No	Size	List
200971	18387	5 oz. Tube	\$9.30
200945	18388	10 oz.	\$13.43



### Permatex Clear RTV Silicone Adhesive Sealant

General-purpose, clear RTV indoor/outdoor sealant. Seals, bonds, repairs, mends and secures glass, metal, plastics, fabric, vinyl, weather stripping and vinyl tops. Protects and repairs electrical wiring. May be applied to horizontal or vertical surfaces. Waterproof and flexible. Temperature range -80° F to 450° F, resists oil, water, weather, vibration, grease. Suggested applications: windshields, door frames, electrical connections, vinyl tops, seams and roofs.

Order No	Mfg No	Size	List
220261	80050	3 oz.	\$6.57



954-463-4307 • D.S. Hull Company, Inc. • www.dshullco.com

# Maintenance

BOATLIFE SOLVENT • BOATLIFE LIFE CALK • BOATLIFE LIFE SEAL • BOATLIFE GET ROT • MIXING STICKS • CONTACT CEMENT

Like Us On Facebook


954-463-4307 • D.S. Hull Company, Inc. • www.dshullco.com



### BoatLife Life Calk

Long lasting, permanently flexible marine polysulfide sealant which can be sanded, painted and used above and below the waterline. Tack-free in 1 to 3 days. Cure time dependent on quantity applied, temperature and humidity. Offers excellent resistance to teak oils, gasoline and diesel fuel. Used to bed deck and hull hardware, seal thru-hull fittings on wood and fiberglass boats and to seal wooden boat and deck seams. Bonds to fiberglass, wood, metal, glass and itself. Cures to firm flexible rubber seal with excellent waterproofing and adhesion qualities. Apply to clean surface for best results. Do not use on Lexan or ABS. Can be applied to damp surfaces.

Order No	Mfg No	Color	Size	List
230002	1030	White	2.8 oz. Tube	\$15.80
230003	1031	Black	2.8 oz. Tube	\$15.80
230004	1032	Mahogany	2.8 oz. Tube	\$15.80
230009	1037	Teak	2.8 oz. Tube	\$15.80
230005	1033	White	10.4 oz. Cartridge	\$29.33
230006	1034	Black	10.4 oz. Cartridge	\$29.33
230007	1035	Mahogany	10.4 oz. Cartridge	\$29.33
230008	1036	Teak	10.4 oz. Cartridge	\$29.33



### BoatLife Liquid Life Calk Sealant

Non-shrinking, flexible, sandable compound. Low viscosity, free-flowing polysulfide sealant for use on fine cracks and seams.

Order No	Mfg No	Color	Size	List
230031	1052	White	2.8 oz. Tube	\$13.03



### BoatLife Life Calk Solvent and Cleaner

Removes uncured polysulfide sealant and grease from tools and equipment. Use as a cleaner to prepare seams for caulking. Use only in a well ventilated area.

Order No	Mfg No	Size	List
230033	1056	Pint	\$28.23



### BoatLife Life-Seal Sealant

Unique combination of marine silicone and polyurethane, formulated especially for fiberglass. Fast-curing, low odor, high adhesion, non-sagging, non-corrosive, non-yellowing formula. Provides durable, permanent, watertight seal for joints subject to structural movement. May be used above and below the waterline. Use for sealing decks to hulls, thru-hull fittings, vinyl ports, sealing/glazing windshields and bedding marine hardware. Adheres to metal, glass, wood, Lexan, ABS and other materials. Can be removed without damaging gelcoat. Not recommended for ferro cement hulls, impregnated wood or oil soaked materials.

Order No	Mfg No	Color	Size	List
230024	1160	Clear	2.8 oz. Tube	\$13.75
230025	1161	White	2.8 oz. Tube	\$17.99
230026	1162	Black	2.8 oz. Tube	\$13.75
230027	1169	Clear	10.4 oz. Cartridge	\$25.65
230028	1170	White	10.4 oz. Cartridge	\$25.65
230029	1171	Black	10.4 oz. Cartridge	\$25.65



### BoatLife Silicone Rubber Sealant

All-purpose, non-corrosive, low-odor marine silicone sealant. Tack-free in 30 minutes or less. Fully cured in 24 hours. For above the waterline applications. Will not shrink, crack, dry out or yellow. Superior flexibility and adhesion to fiberglass, plastic, metal and wood. Retains hardness, flexibility and tensile strength even after years of exposure. Is not sandable or paintable.

Order No	Mfg No	Color	Size	List
230018	1140	Clear	2.8 oz Tube	\$10.68
230019	1141	White	2.8 oz Tube	\$10.68
230020	1142	Black	2.8 oz Tube	\$10.68
230021	1150	Clear	10.4 oz. Cartridge	\$20.38
230022	1151	White	10.4 oz. Cartridge	\$20.38
230023	1152	Black	10.4 oz. Cartridge	\$20.38



### BoatLife Git Rot

Two-part liquid epoxy saturates and restores original strength to wood by penetrating the rot. Not necessary to remove loose rotted fibers. Wood must be dry. Apply by injecting into wood. Will soak into wood by capillary action. One-half hour pot life after mixing. Cures overnight. Sandable and paintable, can be drilled and screwed. Compatible with fiberglass resins, epoxies and most sealants. Great for transoms, stringers and cabin roof rot in both fiberglass and wood boats.

Order No	Mfg No	Size	List
230013	1063	4 oz.	\$24.15
230032	1064	Pint	\$55.18



### Caulking Cartridge (Empty)

10.6 oz. For use in standard caulking gun.

Order No	Mfg No	List
230030	1120	\$3.20



### Caulk Savers

Works to seal any glue, cement, caulk, cement, adhesives and silicone that comes in a caulk type cartridge.

Order No	Mfg No	List
221698	CS055	\$2.39



### US Chemicals Mixing Board

Special non-stick, non-absorbent plastic surface. Just flex to clean. Ideal for epoxies and polyester compounds. 12" x 12"


Order No	Mfg No	List
369825	37005	\$6.80



### Jumbo Mixing Sticks

Wood. 6" x 3/4". 10 per package.

Order No	Mfg No	List
250001	JMBCRFTSTCK	\$1.19



### DAP Weldwood Contact Cement

High strength and initial grab make it ideal for most projects. Fast-drying formula dries in 15-20 minutes. Offers high heat and water resistance when dry.

Order no.	Mfg. No.	Size	List
200947	00107	3 oz.	\$7.24
200928	271	Pint	\$12.93
200929	00272	Quart	\$17.79

# Maintenance

GORILLA GLUE • WOOD GLUE • SILICONE ADHESIVE SEALANT • TRIM ADHESIVE SPRAY • SUPER GLUE GEL • BEDDING COMPOUND



### 3M High-Strength Adhesive #90

Fastest drying, high-strength adhesive. Dries in one to two minutes. Bonds difficult substrates such as polyethylene, polypropylene, many other plastics. Adjustable tip allows selection of a 1 to 3 inch spray width to match any application requirement. Contains no methylene chloride, 1,1,1-trichloroethane or chlorofluorocarbons.

Order No	Mfg No	Size	List
201879	30023	17.6 oz.	\$38.12



### General Trim Adhesive Spray

Fast drying, high-strength, 50% VOC clear adhesive in an aerosol container. For bonding most types of trim used on boats except unsupported vinyl. Excellent for fabrics, upholstery foam, carpets. Do not use on styrofoam.

Order No	Mfg No	Size	List
201833	08088	18.1 oz.	\$36.30



### Amazing Goop Adhesive

Strongest single component adhesive. Bonds to metal, canvas, wood, vinyl, and rope. UV resistant. May be painted over. Seals with a tight, flexible waterproof hold. Repairs vinyl seats, canopies and canvas covers. Seals around windshields and port-holes. Seal diving masks and hoses. Apply coating to frayed ropes. Cover battery terminals to prevent sparking. Secure hoses to dock lines.

Order no.	Mfg. No.	Size	List
333557	170012	3.7 oz.	\$7.99



### Loctite Super Glue Gel

A clear, one-part adhesive gel that dries within minutes after joining to form strong, permanent bond between close-fitting, non-porous surfaces. Has good resistance to chemicals, water and lower-temperature extremes. 2 gram tube.

Order No	Mfg No	List
201964	235495	\$2.49



### White Gorilla Glue

Bonds materials other adhesives simply can't; metal, stone, wood, ceramics, foam, glass and much more! It's still the best glue for anyone who wants the job done right.

Order no.	Mfg. No.	Size	List
239201	5201205	2 oz.	\$8.49



### Gorilla Glue 2-Part Epoxy Glue

Impact-tough formula, providing high impact resistance and strength to handle the toughest projects. Sets in 5 minutes and can be handled in 90 minutes. Gap filling capabilities and all purpose formula that easily bonds steel, wood, aluminum, ceramic and much more. Water resistant; withstands moderate exposure to water.

Easy-to-use reusable syringe - separate barrels of resin and hardener keep epoxy from hardening, plus syringe dispenses evenly and includes a cap for multiple uses.

Order no.	Mfg. No.	Size	List
239246	4200102	.85 oz.	\$7.49



### Loctite Super Glue

Gel control; prevents drips or runs. Impact and water resistant. Flexible. Works on metal, rubber, ceramics, wood, leather, paper and most plastics.

Order no.	Mfg. no.	Size	List
202613	19026	.14 oz.	\$5.99



### Repair Wrap

Combines industrial-strength fibers and specialized resin into a repair patch that hardens like steel - providing a permanent fix. Simply activate the repair wrap in water, wrap tightly around the broken object and your item will be repaired within 10-15 minutes.

Order no.	Size	List
222472	1 Roll (1" x 40")	\$8.75



### Titebond II Premium Wood Glue

One-part wood glue that passes the ANSI Type II water-resistance specification. Ideal for exterior projects. Titebond II Premium provides a strong initial tack, fast speed of set, superior strength and excellent sandability. It is FDA approved for indirect food contact (cutting boards) and is ideal for radio frequency (R-F) gluing.

Order no.	Mfg. No.	Size	List
287250	500-2	4 oz.	\$4.19
287252	500-4	16 oz.	\$9.99



### Titebond III Ultimate Wood Glue

The first one-part, water cleanup wood glue ever offered that is proven water-proof. The water-proof formula passes the ANSI/HPVA Type I water-resistance specification and offers superior bond strength, longer open assembly time and lower application temperature. Titebond III is non-toxic, solvent free and cleans up with water - safer to use than traditional water-proof glues. It provides strong initial tack, sands easily without softening and is FDA approved for indirect food contact (cutting boards). The ultimate in wood glues - ideal for both interior and exterior applications.

Order no.	Mfg. No.	Size	List
287261	1412	4 oz.	\$5.75
287273	1413	8 oz.	\$8.99



### Dap Weldwood Spray Contact Cement

Easy-to-use spray can! High-strength, high-temperature-resistant formulation that bonds most woods, particle board, metal, laminate & many plastics including polyethylene and polypropylene.

Order no.	Mfg. No.	Size	List
200918	122	16 oz.	\$19.55



### Whitaker Epoxy Glue

A two-part epoxy, excellent for filling holes and cracks in any wood, fiberglass, metal or cement. Will not sag or shrink. Fast curing and easily sanded when dry.

Order no.	Mfg. No.	Size	List
233249	605900700	Pint	\$27.25
108096	605910700	Quart	\$43.75
297003	605920700	Gallon	\$135.00



### Dolphinite Natural Bedding Compound

Flexible, semi-paste type, slow oxidizing waterproof compound for bedding in joints, in keel, keelson, stern, sternpost, transom, battens and other hull members. Also for bedding in deck fittings, mouldings, and trim around deck houses. May be used on wood, fiberglass and metal or wherever a waterproof seal is required. Apply by hand, pressure gun or putty knife. Thinning is not normally required.

Order no.	Mfg. No.	Size	Color	List
706651	2005NQ	Quart	Natural	\$72.35

Like Us On Facebook

954-463-4307 • D.S. Hull Company, Inc. • www.dshullco.com

# Maintenance

## EPOXY SYRINGES

Like Us On Facebook

954-463-4307 • D.S. Hull Company, Inc. • www.dshullco.com



**Devcon 5 Minute Epoxy Gel Syringe**  
2500 psi strength.  
Mixing tray and stick included.  
Blue dye indicator disappears as mixed.  
Good solvent resistance to gas, oil and other solvents.  
Non-sag so it works well on vertical surfaces.  
Excellent gap filling quality.  
Fast curing.

Order no.	Mfg. No.	Size	List
120017	21045	25ml	\$7.25



**Devcon 5 Minute Epoxy Syringes**  
1500 psi strength  
Two part, rapid curing clear, general purpose epoxy.  
Better on more rigid materials.  
Useful for repair of autos, bikes, boats and more.  
May also be used as a metal filler and to restore rotten wood.  
Bonds: metals, wood, glass, ceramic, concrete, stone, china and fiberglass.  
Tensile strength: 1500 psi  
Color: clear  
Handling time: 5 minutes  
Set time: 8-10 minutes  
Cure time: 1 hour

Order no.	Size	Size	List
222846	20845	25ml	\$7.25



**Devcon 2 Ton Epoxy Flow-Max Syringe**  
Bonds: acrylic, china, fiberglass, metal, wood, concrete, ceramic and glass.  
Tensile strength: 2500 lbs.  
Color: Clear to a light yellow.  
Water resistant.  
Handling time: 30 min.  
Set time: 30 min.  
Full cure: 24 hours.  
Temperature range -60°F to 180°F

Order no.	Size	Size	List
222880	23145	14ml	\$7.25
222902	31345	24ml	\$7.25



**Devcon 60 Second Epoxy Flow-Mix Gel Syringe**  
Super fast, clear, non-shrinking general purpose epoxy that provides instant adhesion.  
Complete with a blue dye indicator, the blue color disappears when epoxy is thoroughly mixes.  
Water resistant.  
Fills gaps.  
Bonds: metal, wood, glass, ceramic, fiberglass.  
Tensile strength: 1250 psi.  
Set time: 2-5 minutes.  
Cure time: 1 hour.

Order no.	Mfg. No.	Size	List
222857	21445	14ml	\$7.25



**Devcon 2-Part Plastic Welder**  
Bonds: hard plastic, styrene, PVC, acrylic, ceramic, concrete, fiberglass, metal, vinyl, wood.  
Tensile strength: 3500 psi  
Color: cream  
Waterproof  
Handling time: 4-5 minutes  
Set time: 10-15 minutes  
Cure time: 24 hours  
Temperature range: -40° F to 200° F

Order no.	Size	Size	List
222868	22045	25ml	\$7.25



**Devcon Flow-Mix Cold Weld Epoxy**  
Bonds: steel, copper, aluminum, bronze, metal, iron.  
Tensile strength: 1500 lbs.  
Color: Dark gray.  
Water resistant.  
Handling time: 4-5 min.  
Set time: 8-10 min.  
Full cure: 1 hours.  
Temperature range 40°F to 200°F

Order no.	Size	Size	List
222891	24445	14ml	\$7.25



**Devcon 5 Minute Flow-Mix Epoxy Syringes**  
1250 psi strength.  
Two part, rapid curing clear, general purpose epoxy.  
Better on more rigid materials.  
Useful for repair of autos, bikes, boats and more.  
May also be used as a metal filler and to restore rotten wood.  
Bonds: metals, wood, glass, ceramic, concrete, stone, china and fiberglass.  
Tensile strength: 1500 psi  
Color: clear  
Handling time: 5 minutes  
Set time: 8-10 minutes  
Cure time: 1 hour

Order no.	Size	Size	List
222835	20445	14ml	\$7.25



**Devcon H2 Hold Epoxy**  
Bonds: PVC, metal, wood, glass, fiberglass, ceramic, acrylic, plastic, masonry, fabric..  
Tensile strength: 1800 psi  
Color: off-white  
Waterproof  
Cures and bonds underwater  
Handling time: 15-30 minutes  
Set time: 1-2 hours  
Cure time: 24 hours  
Temperature range: 40° F to 200° F

Order no.	Size	Size	List
222879	22445	25ml	\$12.25



**Devcon Plastic Steel Epoxy**  
Bonds: metal, Iron, Steel, Stainless Steel, Brass, Pewter and Aluminum..  
Tensile strength: 2600 lbs.  
Color: Black (Dark gray).  
Water resistant.  
Handling time: 60 min.  
Set time: 4-6 hours..  
Full cure: 16-24 hours.  
Temperature range 200°F constant; 250°F intermittent

Order no.	Size	Size	List
222913	62345	25ml	\$7.25